



BEYOND THE EXPECTED.™

Ex450 UTILITY TRACTOR ATTACHMENTS



CL400 Loader (Order Bucket Separately)

Curved boom construction allows for better bucket visibility and clear sight lines. Features a 72" square back bucket with a capacity of 10.6" cu. ft. QuickAttach™ system and optional universal QuickAttach™ make attaching and removing the loader quick and easy. QuickAttach™ pallet forks, bale spear and high-volume bucket also available.



CB85 Backhoe

QuickAttach™ system allows you to install or remove the backhoe in minutes as it sets in the cradle with two locking pins. Single Power Beyond kit powers the backhoe for reliability, control and smooth operation. Dual swing cylinders allow for precise control of backhoe along foundations and provide more power for backfilling. Curved boom assembly gives the operator better sight lines when digging.



FML72 Rear Finishing Mower

Features an 8-gauge deck housing and reinforcement plate under the spindle assembly. Rear discharge disperses cuttings cleanly and evenly. Comes with a wide range of cutting heights from 1" to 5" for clean cuts on all lawns. Gearbox is highly engineered and rugged with straight-cut gears, casted cooling fins and completely enclosed seals. The four durable composite rubber caster wheels give a perfectly level cut while eliminating the worry of flat tires. Category 1, full floating deck allows the mower to follow the contours of the land.



RC72 72" Rotary Cutter

Deck housing is constructed from 10-gauge steel and reinforced with a 10-gauge plate under the gearbox assembly. Features a cutting height adjustment from 1" to 9-1/4" with oval stump jumper. Heavy-duty drive line with shear bolt protection transfers power smoothly and protects the valuable components of the tractor. Hardened spring steel blades are mounted on high-carbon steel rotors. Floating top link allows for rotary cutter to follow the contours of the land for clean and even cutting. Laminated tail wheel is puncture resistant and long wearing in harsh brush-cutting conditions.



RT74 74" Tiller

Designed as a 3-in-1 tiller to combine the capabilities of a center tiller, an offset tiller and a reversible rotation tiller to deliver a smooth, finished surface under any ground condition. Offset up to 22", providing visibility when tilling along driveways or structures. The 32 heavy-duty knives blend the soil to create stronger root systems. Adjusts to a maximum depth of 7-1/4" and has a working width of 74"



RB84 84" Rear Blade

The ½" steel A-frame is welded to two 4" x 4" steel beams with ¼" thick walls that are fully reinforced. The rotation plate is constructed from 5/8" thick steel. The 5 forward and 5 reverse positions allows for precise and consistent grading. The angling plate is constructed from ¼" steel. The 4" outer tubes and 3.5" inner tube with ¼" thick walls are center cap welded. The 3-position tilt adjustment provides a wide range of applications. The ¼" rolled moldboard is attached by a ¼" mounting plate. The ½" x 6" cutting edge is hardened for long life and reversible for even greater life expectancy.



BS72 Box Scraper

Heavy-duty A-frame is constructed from ½" thick steel for greater control and strength during grading and backfill operations. The A-frame and box are attached with a 5/8" steel frame making the scraper extremely rigid for uncompromising control. The 4" x 4-1/2" cross beam is the main structural component. The box is made out of ¼" thick steel with ¼" thick reinforcement brackets at each corner. The 5/8" hardened steel ripping shanks with replaceable tips allow them to dig into the toughest soil conditions. Reversible hardened blades give longer life.



LR84 Landscape Rake

The A-frame is constructed from ¼" steel welded to a 3" x 3-1/4" beam for extremely rigid and precise control of the attachment. The rotation plate is constructed from ½" steel. The 5 forward and 5 reverse positions add versatility for a wide variety of chores. The superior construction of the ¾" steel angle iron mounting plate gives rigid support to the tines. The hardened tines are 5/16" x 1" and spaced 2" on center for a high resistance to wear and a cleaner collection of material.



PHD200 Post Hole Digger

Heavy-duty, 2-7/8" x ¼" walled construction of the boom and 2-3/8" x ¼" wall yoke allow for extra strength in all soil conditions. Grade 2 shear bolt provides greater protection to the tractor drive and gearbox assembly. Reinforced mounting collar with double flighting keeps the auger end from wearing out. Hardened replaceable cutting knives allow for fast, clean digs and easy maintenance. Dependable cast-iron gearbox with 540 RPM gives constant digging power. Large 2" output shaft allows for long life in any soil condition.



HC400 Hard Cab Assembly

The steel-constructed roof is lined with a fabric headliner to help reduce drivetrain noise and increase operator comfort and overall appearance. Steel doors with fixed glass allow for a tighter seal over fabric door construction and provide better climate control. Front windshield with tempered glass is clearer and more durable, and provides better performance from the wiper assembly with less window flex. Standard front windshield wiper with single speed provides for clearer sight lines in adverse conditions. Soft rear removable panel makes it a snap to open the cab in warmer conditions.

SS340 Sunshade

The Cub Cadet Yanmar Sunshade is designed with a custom-fit frame assembly to enhance the product's look and increase the ease of installation. The textured finish reduces scratches and keeps the product looking better longer.

For more information about compact or utility tractors from Cub Cadet Yanmar, [contact a dealer](#) in your area.