



BEYOND THE EXPECTED.™

SC2400 / Sc2450 SUB COMPACT TRACTOR ATTACHMENTS



CL100 Loader

Curved boom is constructed from 2" x 5" A500 structural steel, one-piece beam. A 3" round tube with ¼" wall structural steel torque beam attaches the curved boom beams together. Features a heavy-duty 5 cu. ft. bucket with reinforced wear plates. Curved boom design allows for bucket visibility and clear sight lines. QuickAttach™ system also included.



MM60RSe Mid-Mount Mower

Mid-mount 60" deck with superior vacuum for a cleaner cut. Features an 11-gauge stamped reinforced deck edge and long-lasting roller bearings. Cast-aluminum spindle housings with 7/8" shaft allows for cooler operation. Pulleys are machined from one piece of steel for balance, reducing vibration and wear to the shaft. Includes cast-aluminum gearbox housing with roller bearings and 7/8" input and output shafts. Marbane high-lift blades harden to a Rockwell 50 rating. This extends the life of the blade while giving a clean cut. QuickAttach™ system allows the deck to be installed and removed quickly. SmartJet™ deck wash system allows a garden hose to be attached to the deck for high-pressure cleaning.



FM48 Rear Finishing Mower

Features an 11-gauge deck housing and reinforcement plate under the spindle assembly. Rear discharge disperses cuttings cleanly and evenly. Includes a wide range of cutting heights from 1" to 4" for clean cuts on all lawns. Gearbox is highly engineered and rugged with straight-cut gears, cooling fins and completely enclosed seals. The four durable composite rubber caster wheels give a perfectly level cut while eliminating the worry of flat tires. Category 1, full floating deck allows the mower to follow the contours of the land.



BS48 Box Scraper

Heavy-duty A-frame is constructed from ½" thick steel for greater control and strength during grading and backfill operations. The A-frame and box are attached with a 5/8" thick steel frame making the scraper extremely rigid for uncompromising control. The 4" x 4-1/2" cross beam is the main structural component. The box is made out of ¼" thick steel with ¼" thick reinforcement brackets at each corner. The 5/8" hardened steel ripping shanks with replaceable tips allow them to dig into the toughest soil conditions. Reversible hardened blades give longer life.



Curved Boom Backhoe

The 3.6' backhoe's curved boom design provides greater reach in the excavation area, the ability to avoid obstacles, deeper dig capabilities, improved lift height and enhanced sight lines. Easy-to-use controls include a float position on the backhoe boom control. This enables anyone to perform fine leveling and grading with virtually no learning curve and gives experienced users the same advantages that they're used to in large backhoe units. (Sc2450 only)



RB60 60" Rear Blade

The ½" steel A-frame is welded to two 4" x 4" steel beams with ¼" thick walls that are fully reinforced. The rotation plate is constructed from 5/8" thick steel. The 3 forward and 3 reverse positions allows for precise and consistent grading. The angling plate is constructed from ¼" steel. The 4" outer tubes and 3.5" inner tube with ¼" thick walls are center cap welded. Includes a 3-position tilt adjustment for a wide range of applications. The ¼" rolled moldboard is attached by a ¼" mounting plate. The cutting edge is ½" x 6" and is hardened for long life and reversible for even greater life expectancy.



SB45 45" Front-Mounted Snowblower

Wide 45" housing is designed to make a wide 45" clearing path, allowing 5" wider than the tractor. Reinforced augers and steel rods are welded to the augers and the auger mounting shaft, making the augers stronger in heavy snow and frozen conditions. PTO-driven power delivered by the tractor's mid-PTO provides smooth, consistent power. Heavy-duty #50 chain final drive delivers stronger, more reliable horsepower for longer life. QuickAttach™ hitch allows for fast attachment and removal of snowblower.



FB60 60" Dozerblade

Heavy-duty moldboard allows for longer life in all working conditions. The ¼" high-carbon reversible cutting edge gives the blade longer life. Hydraulic power angle provides the operator smooth, precise control. Power down pressure allows the blade to dig into the ground to loosen packed snow or hard dirt. QuickAttach™ hitch makes attaching and detaching easy and fast, and is compatible with the SB45 for added versatility.



GCS24 Triple-Bagger Grass Collection System

Modular design is constructed for greater strength and faster installation and removal. The 3 heavy-duty bags come standard with grab handles on the bottom for better control. The 7" wide exhaust chute with built-in baffle in the hood assembly allows for precise control of grass clippings for more complete bag filling. Features a cloth hood assembly for greater ventilation of collection system. Heavy-duty steel 12" blower impeller and housing is designed for longer life. Comes with a built-in parking stand for easy storage.



HC100 Hard Cab Assembly

The steel-constructed roof is lined with a fabric headliner to help reduce drivetrain noise and increase operator comfort and overall appearance. Steel doors with fixed glass allow for a tighter seal over fabric door construction and provide a better climate control. Front windshield with tempered glass is clearer and more durable, and provides better performance from the wiper assembly with less window flex. Standard front windshield wiper with single speed provides for clearer sight lines in adverse conditions. Soft rear removable panel makes it a snap to open the cab in warmer conditions. (Sc2400 only)

GG10 Grille Guard

Heavy-duty construction helps protect the tractor hood and headlight assembly from potential damage. It's foldable for easy access to the engine, even when the loader is installed.

Swivel Seat

A swivel seat makes switching from loader operation to backhoe operation quick and easy. Simply release the seat lock and spin the seat around for easy access and comfortable reach to the backhoe controls.

Foldable ROPS

For added comfort, wide foldable ROPS and a spacious operator station provide plenty of head and leg room. Also convenient for working under low obstacles and for storage.