

TANK™  
SPREADER/SPRAYER  
XP STAND-ON  
SPREADER/SPRAYER  
XP STAND-ON SPREADER  
TR20 TURF RENOVATOR  
80-LB. SPREADER  
COMMERCIAL SPRAYERS

**FEATURES**

SPREADERS FOR  
SEEDING, FERTILIZING  
OR DE-ICING

25-, 50-, 100-, 200- AND  
300-GAL. SPRAYERS

WANDS AND SPRAY  
GUNS FOR ANY JOB

PREMIUM KAWASAKI®  
OHV ENGINES,  
ELECTRIC OR  
RECOIL START

1-YEAR LIMITED  
COMMERCIAL  
WARRANTY, NO HOUR  
LIMITATIONS†



**GET MORE DONE. GET MORE BUSINESS.  
WITH THIS FULL LINE OF APPLICATION EQUIPMENT.**

When you're focusing on better results like growing profitability and client satisfaction, start with better products. Innovative and highly reliable Cub Cadet Commercial application equipment will help you save time, improve productivity and improve your level of service — which will all help to boost your bottom line.

**INNOVATIVE FEATURES FOR AN INCREDIBLE EXPERIENCE. THAT'S THE CUB CADET ADVANTAGE.**



**TANK™ SPREADER/  
SPRAYER**

Cover large areas in one pass with a 40-gallon tank and a 125-lb. capacity hopper — all powered by a 17 HP\* Kawasaki® V-Twin engine.



**XP STAND-ON  
SPREADER/SPRAYER**

This 3-in-1 application machine also features dual, independent 5-gallon tanks, boomless spray nozzles and a spray wand.



**80-LB. SPREADER**

This 80-lb.-capacity polyethylene hopper with an easy-to-use rate adjustment mechanism gives you simple, precise control over the output or flow of material.



**TR20 TURF RENOVATOR**

Equipped with an 8 HP\* Kawasaki® engine and a 35-lb. hopper capacity, the TR20 Turf Renovator dethatches, slices and seeds like a pro.



**COMMERCIAL SPRAYERS**

With 25 to 300 gallon options — most with a high-performance 5.5 HP\* Kawasaki® engine — our sprayers are ideal for light-duty to heavy-duty use.



**XP STAND-ON SPREADER**

Powered by a 6 HP\* Kawasaki® engine, this premium 125-lb. hopper seeds and fertilizes. Includes a sulky-style riding platform and rear-wheel drive for traction.

†See specifications for warranty information.

\*as rated by engine manufacturer

	80-lb. Rotary Spreader	XP Stand-On Spreader	XP Stand-On Spreader/Sprayer	TR20 Turf Renovator	TANK™ Spreader/Sprayer
Engine	-	6 HP* Kawasaki®	6 HP* Kawasaki®	8 HP* Kawasaki®	17 HP* Kawasaki®
Engine series	-	Vertical OHV	Vertical OHV	Horizontal OHV	Vertical OHV
Ignition	-	Recoil start	Electric start/recoil	Recoil start	Electric start
Cylinder	-	Single	Single	Single	Twin
Gear reduction	5:1 ratio	-	Electric motor	-	-
Oil filter	-	Yes	-	-	Yes
Hopper/tank width	-	-	Dual 5-gal. tanks/fender mounted	20" dethatching/seeding	-
Hopper size	80 lbs.	125 lbs.	125 lbs.	35 lbs.	125 lbs.
Tank size	-	-	Dual 5-gal. tanks/independent	-	40 gal.
Tank shape	Rectangular hopper	Rectangular hopper	Rectangular hopper	Rectangular	Rectangular
Strainer	Stainless mesh screen	Stainless mesh screen	Stainless mesh screen	-	-
Agitation	Oscillating agitator	Oscillating agitator	Oscillating agitator	-	Triple jet & oscillating agitator
Hopper/tank material	Polyethylene	Polyethylene	Polyethylene	Steel	Polyethylene
Frame type	Stainless steel	Stainless/welded steel	Stainless/welded steel	Welded steel	Welded steel
Frame material	1" SS tube	1" SS tube & 7-ga. steel	1" SS tube & 7-ga. steel	11-ga. painted steel	Painted steel
Drive system	Push	Hydro-Gear™ transmission	Hydro-Gear™ transmission	Hydraulic with chain-driven differential	Kanzaki DUP-10 pumps & White® wheel motors
Speeds	-	Fwd: 5 mph, Rev: 3 mph	Fwd: 5 mph, Rev: 3 mph	Fwd: 2 mph, Rev: 1 mph	Fwd: 10 mph, Rev: 4 mph, lock-in application speed
Front wheels	13" x 5.0" - 6"	13" x 6.5" - 6"	13" x 6.5" - 6"	13" x 5.0" - 6"	13" x 6.5" - 6"
Rear wheels	-	18" x 6.5" - 8"	18" x 8.5" - 8"	13" x 5.0" - 6"	24" x 12" - 12"
Pump output	-	-	-	-	4.8 GPM, 40 psi
Pump type	-	-	12 VDC Flojet™ pump	-	12 VDC Flojet™ pump
Hose size	-	-	25-ft. coil hose w/spot wand	-	25-ft. coil hose
Hose material	-	-	PVC	-	PVC
Pressure rating (hose)	-	-	100 psi	-	100 psi
Length x width x height	48" x 25" x 35"	56" x 35" x 48"	56" x 35" x 48"	31" wide overall	99" x 57" x 48"
Effective spray/spread width	-	120"	120"/108" boomless spray	-	120"
Weight	32 lbs. dry	340 lbs. dry	365 lbs. dry	290 lbs. dry	1,134 lbs. dry
Spray wand/gun	-	-	Spot spray wand & 3 boomless spray nozzles	-	Adj. spot spray wand & 3-section boom 5 nozzle
Warranty†	1-year limited commercial, no hour limitations				

SPRAYERS	25 Spot	50 Poly	100 Poly	200 Poly	300 Poly	200 Compact
Engine	12 VDC	4 HP* Kawasaki®	5.5 HP* Kawasaki®	5.5 HP* Kawasaki®	5.5 HP* Kawasaki®	5.5 HP* Kawasaki®
Engine series	-	Horizontal OHV	Horizontal OHV	Horizontal OHV	Horizontal OHV	Horizontal OHV
Ignition	-	Recoil start	Recoil start	Recoil start	Recoil start	Recoil start
Cylinder	-	Single	Single	Single	Single	Single
Gear reduction	-	6:1 direct-coupled	6:1 direct-coupled	6:1 direct-coupled	6:1 direct-coupled	6:1 direct-coupled
Tank size	25 gal.	50 gal.	100 gal.	200 gal.	300 gal.	200 gal.
Tank shape	Rectangular					
Strainer	In-line SS on inlet side of pump	Stainless steel mesh	Stainless steel mesh	Stainless steel mesh	Stainless steel mesh	Stainless steel mesh
Agitation	-	Triple jet spray	Triple jet spray	Triple jet spray	Triple jet spray	Triple jet spray
Hopper/tank material	Polyethylene					
Frame type	-	Welded steel	Welded steel	Welded steel	Welded steel	Welded steel
Frame material	-	Painted steel	Painted steel	Painted steel	Painted steel	Painted steel
Pump output	4.8 GPM/40 psi	Max. 6 GPM	Max. 9.5 GPM	Max. 9.5 GPM	Max. 9.5 GPM	Max. 9.5 GPM
Pump type	Diaphragm	Twin diaphragm	Twin diaphragm	Twin diaphragm	Twin diaphragm	3-diaphragm
Pump pressure	60 psi	Max. 275 psi	Max. 550 psi	Max. 550 psi	Max. 550 psi	Max. 550 psi
Hose reel	-	Hannay® electric	Hannay® electric	Hannay® electric	Hannay® electric	Hannay® electric
Hose size	1/4" i.d. x 25'	3/8" i.d. x 300'	1/2" i.d. x 300'	1/2" i.d. x 300'	1/2" i.d. x 300'	1/2" i.d. x 300'
Hose material	Flexcoil - PVC	PVC	PVC urethane core	PVC urethane core	PVC urethane core	PVC urethane core
Pressure rating (hose)	100 psi	300 psi	800 psi	800 psi	800 psi	800 psi
Length x width x height	30" x 20" x 19"	54" x 19" x 26"	48" x 38" x 34"	65" x 39" x 40"	88" x 38" x 47"	62" x 40" x 40"
Weight w/o hose & reel	22 lbs. dry	125 lbs.	237 lbs.	336 lbs.	422 lbs.	330 lbs.
Weight w/hose & reel	-	200 lbs.	371 lbs.	470 lbs.	556 lbs.	454 lbs.
Spray wand/gun	Trigger jet w/conejet nozzle	Order as needed	Order as needed	Order as needed	Order as needed	Order as needed
Warranty†	1-year limited commercial, no hour limitations					

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.