



ATTACHMENTS

Depending on the time of year or your geographic location, being productive can be a matter of having the right accessories. So whether it's challenging terrain, needing to work past dusk, collecting leaves or even plowing snow, Cub Cadet Commercial accessories make your job easier — and a lot more enjoyable.



LIGHT KIT
Easy-to-install kit provides increased visibility and safety for early or late days.



MULCHING KIT
Mulching baffles install easily to control airflow and reliably re-cut clippings for superior mulching.



12-VOLT OUTLET
Adding electrical power to your TANK™ is simple and easy.



ULTRA-TRACTION TIRES
Deliver improved traction on hills, or in sandy or snowy conditions.



72" BLADE
The steel blade attaches for light dozer work and snow plowing, with skid shoes for height adjustment.



TRIPLE BAGGER
Large, 10-bushel, triple-bag grass collection system for a professional, well-groomed look.



SPREADER
Attaches to either front or rear of the TANK™ to spread salt, seed or fertilizer.



POWER ASSIST DUMP HOPPER
Easily transports and unloads grass clippings or leaves.



ELECTRIC LIFT CYLINDER
Useful all year long. It raises the deck or snow blade easily.

Cub Cadet
COMMERCIAL



YOUR CLIENTS WON'T JUST BE SATISFIED, THEY'LL BE SPEECHLESS.

If you're looking for a top-of-the-line commercial zero-turn rider, you've found it. The TANK™ is designed to do it all. The Select Cut System™ deck can cut all types of grass in all types of conditions. Plus, it produces a high-quality cut at faster ground speeds. It easily handles attachments without sacrificing productivity, and has features that keep the operator comfortable in rough conditions. And with true commercial-grade toughness, it's no wonder that the TANK™ is the mower that all other mowers aspire to be.

INNOVATIVE FEATURES FOR AN INCREDIBLE EXPERIENCE. THAT'S THE **CUB CADET ADVANTAGE.**



PIVOTING FRONT AXLE

Follows the contours of the ground for superior cutting, providing a smoother, more uniform look and versatility for different terrain. Leaving you with professional results every time and everywhere.



SELECT CUT SYSTEM™ DECK

The innovative sloped-nose deck features a configurable inner baffle, offset and adjustable leading edges, ball wheels and the SmartJet™ deck washing system. Giving you a premium cut in the toughest grass-cutting conditions from a deck that's easy to service.

Only available on the TANK™ M series.



FULL SUSPENSION SEAT

This premium seat allows the operator to customize suspension settings for weight and personal preference. It also features foldable armrests and tilt capability for lower back support. Giving you the maximum comfort and support even during those long workdays.

TANK™

COMMERCIAL ZERO-TURN RIDERS

- TANK™ L48
- TANK™ L60
- TANK™ M54
- TANK™ M60
- TANK™ M72

FEATURES

48" 54" 60" OR 72" FABRICATED DECK SIZE

ENGINE OPTIONS UP TO 37 HP*

PIVOTING FRONT AXLE FOLLOWS CONTOURS OF THE GROUND

CUTS UP TO 6.5 ACRES PER HOUR

FOLDABLE ROPS

FOOT PEDAL DECK LIFT

GROUND SPEEDS UP TO 12 MPH

PATENTED SMARTJET™ DECK WASH SYSTEM

3-YEAR LIMITED COMMERCIAL WARRANTY, NO HOUR LIMITATIONS†

*See specifications for warranty information.

†as rated by engine manufacturer

LOCATE A DEALER AT **CUBCADET.COM**

YOUR INDEPENDENT DEALER CAN ANSWER ALL YOUR QUESTIONS ABOUT THE MANY BENEFITS OF OWNING A CUB CADET.

cubcadetcommercial.com

ENGINE	TANK™ L48	TANK™ L60	TANK™ M54-KH
Engine type	25 HP* Kohler® Command® V-Twin OHV	27 HP* Kohler® Command® V-Twin OHV	27 HP* Kohler® Command® V-Twin OHV
Engine displacement/orientation	724cc/vertical	725cc/vertical	725cc/vertical
Engine fuel	Gas		
Ignition	Transistor controlled		
Lubrication/filter	Full pressure w/spin-on oil filter		
Cooling system	Air		
Air cleaner	Heavy-duty remote-mounted replacement dual element		
Alternator	12V - 20 amp. regulated		
Fuel capacity	Twin 4.25 gal. (8.5 gal. total)	Twin 4.25 gal. (8.5 gal. total)	Twin 7-gallon tanks

DRIVE SYSTEM

Drive system	Hydro-Gear™ PK-12 pumps & Parker wheel motors		
Ground speed	Fwd: 10 mph/Rev: 5 mph	Fwd: 10 mph/Rev: 5 mph	Fwd: 12 mph/Rev: 5 mph
Hydraulic fluid	Shell Rotella® Trip Plus 15W40		
Hydro fluid capacity	3 qt.		
Hydraulic oil filter	Standard		
Controls	3-way adjustable lap bars		
Lap bar dampers	Standard		
Return to neutral	Standard		
Braking/parking brake	Expansion Shoe/Drum		

STEERING

Caster wheel pivot bearings	Tapered roller, greasable		
Front axle	Pivoting/fixed with lockout pins		

CHASSIS

Frame	Fully welded steel 2" square tubing		
-------	-------------------------------------	--	--

TIRES

Front tire size	13" x 6.5" - 6" (smooth)		
Rear tire size	23" x 9.5" - 12" (turf)	24" x 12" - 12" (turf)	24" x 12" - 12" (turf)

DIMENSIONS

Length x width x height	74.5" x 59" x 72"	78" x 65" x 72"	78" x 65" x 72"
Wheelbase	44.5"	48.5"	50.5"
Front track width	40.25"	39"	45.5"
Rear track width	45.5"	46.5"	52"
Weight (approx.)	1,080 lbs.	1,100 lbs.	1,100 lbs.

MOWING DECK

Deck size/type	48" sloped-nose design	60" sloped-nose design	54" Select Cut System™
Deck style/system	Floating		
Deck blades	3-blade		
Deck construction	10-gauge fabricated with 7- and 10-gauge reinforcements		
Deck wash	Patented SmartJet™ high-pressure deck washing system		
Deck lift	Dual pedal, spring assisted		
Deck height adjustment	1" - 5" (in .25" increments)		
Blade spindle construction	Cast-aluminum		
Deck PTO	Electronic fingertip engagement		
Front anti-scalping wheels/nose roller	4 standard, greasable		
Rear anti-scalping rollers/striper	Full width, adjustable		

ADDITIONAL SPECIFICATIONS

ROPS	Standard, foldable		
Monitor/hour meter	Standard, electronic		
Seat type	High-back elasticity vibration control (EVC) suspension seat w/armrests	High-back elasticity vibration control (EVC) suspension seat w/armrests	High-back suspension seat, foldable, fully adjustable with armrests
Cup holder	Standard		
Storage pouch	Standard		
Rear bumper and hitch	Heavy-duty rear bumper w/bolt-on hitch standard		

WARRANTY*

	3-year limited commercial, no hour limitations		
--	--	--	--

ENGINE	TANK™ M60-KH	TANK™ M60-KW	TANK™ M72-KW
Engine type	27 HP* Kohler® Command® V-Twin OHV	31 HP* Kawasaki® V-Twin OHV	37 HP* Kawasaki® V-Twin OHV
Engine displacement/orientation	725cc/vertical	852cc/vertical	999cc/vertical
Engine fuel	Gas		
Ignition	Transistor controlled		
Lubrication/filter	Full pressure w/spin-on oil filter		
Cooling system	Air		
Air cleaner	Heavy-duty remote-mounted replacement dual element		
Alternator	12V - 20 amp. regulated		
Fuel capacity	Twin 7-gallon tanks		

DRIVE SYSTEM

Drive system	Hydro-Gear™ PK-12 pumps & Parker wheel motors		
Ground speed	Fwd: 12 mph/Rev: 5 mph		
Hydraulic fluid with remote cooling system	Shell Rotella® Trip Plus 15W40		
Hydro fluid capacity	3 qt.		
Hydraulic oil filter	Standard		
Controls	3-way adjustable lap bars		
Lap bar dampers	Standard		
Return to neutral	Standard		
Braking/parking brake	Expansion Shoe/Drum		

STEERING

Caster wheel pivot bearings	Tapered roller, greasable		
Front axle	Pivoting/fixed with lockout pins		

CHASSIS

Frame	Fully welded steel 2" square tubing		
-------	-------------------------------------	--	--

TIRES

Front tire size	13" x 6.5" - 6" (smooth)		
Rear tire size	24" x 12" - 12" (turf)		

DIMENSIONS

Length x width x height	78" x 71" x 72"	78" x 71" x 72"	81" x 83" x 72"
Wheelbase	50.5"	50.5"	53.5"
Front track width	45.5"	45.5"	51"
Rear track width	58"		
Weight (approx.)	1,150 lbs.	1,150 lbs.	1,380 lbs.

MOWING DECK

Deck size/type	60" Select Cut System™	60" Select Cut System™	72" Select Cut System™
Deck style/system	Floating		
Deck blades	3-blade		
Deck construction	10-gauge fabricated with 7- and 10-gauge reinforcements	10-gauge fabricated with 7- and 10-gauge reinforcements	9-gauge fabricated with 7- and 10-gauge reinforcements
Deck wash	Patented SmartJet™ high-pressure deck washing system		
Deck lift	Dual pedal, spring assisted		
Deck height adjustment	1" - 5" (in .25" increments)		
Blade spindle construction	Cast-aluminum		
Deck PTO	Electronic fingertip engagement		
Front anti-scalping wheels	4 standard, greasable		
Rear anti-scalping rollers/striper	Full width, adjustable	Full width, adjustable	Full width, adjustable/2 rear corner rollers

ADDITIONAL SPECIFICATIONS

ROPS	Standard, foldable		
Monitor/hour meter	Standard, electronic		
Seat type	High-back suspension seat, foldable, fully adjustable with armrests		
Cup holder	Standard		
Storage pouch	Standard		
Rear bumper and hitch	Heavy-duty rear bumper w/bolt-on hitch standard		

WARRANTY†

	3-year limited commercial, no hour limitations		
--	--	--	--