



Sc2400

SUB-COMPACT TRACTOR

FEATURES

SELECTABLE 4WD

3-POINT HITCH
POSITION CONTROL

HYDRAULIC
POWER STEERING

CRUISE CONTROL

ELECTRO-HYDRAULIC
PTO

REVERSE-OVERRIDE
SWITCH FOR SAFE
PTO OPERATION

ONE-PIECE HOOD
FOR EASE OF
MAINTENANCE

LOW-MOUNTED FUEL
TANK FOR EASY FILL

12-VOLT DC OUTLET

DIFFERENTIAL LOCK

REVERSE-MOUNTED
ENGINE

ILLUMINATED DASH

WIDE OPERATOR'S
STATION

CELL PHONE POCKET
AND CUP HOLDER

5-YEAR LIMITED
POWERTRAIN
WARRANTY†

A SUB-COMPACT TRACTOR WITH BIG TRACTOR FEATURES.

Get big tractor power in the body of a sub-compact with the Sc2400. With Performance Link Technology™, your engine, transmission, hydraulics and fuel injectors are perfectly matched, so you get the most out of every ounce of horsepower. From Shift-On-The-Go® technology to extra worklights, every detail was designed so that you accomplish more than you thought possible.

INNOVATIVE FEATURES FOR AN INCREDIBLE EXPERIENCE IS THE **CUB CADET YANMAR ADVANTAGE.**



24 HP* DIRECT-INJECTION DIESEL ENGINE

This high-performance, 3-cylinder, liquid-cooled diesel engine runs cleaner and more efficiently. The advanced combustion chamber design allows for better fuel atomization and a longer stroke — for better torque reserve. Features like these add up to a powerful experience.



2-RANGE SHIFT-ON-THE-GO®

A Cub Cadet Yanmar exclusive, you'll be able to shift between high and low range without stopping or disengaging cruise control. This is perfect when using the loader, tiller or grading equipment. Shifting that's easier on the engine and safer to operate, so you can focus on what you set out to do.



DUAL HYDRAULIC PUMPS

Separate hydraulic pumps deliver a more efficient flow of hydraulic fluid for a smooth response without compromising horsepower. Whether you're using the curved boom loader or accelerating through rough terrain with power steering, you'll have the power you need to handle demanding jobs with ease.

LOCATE A DEALER AT
CUBCADETYANMAR.COM

YOUR INDEPENDENT DEALER CAN ANSWER ALL YOUR QUESTIONS ABOUT THE MANY BENEFITS OF OWNING A CUB CADET YANMAR.

*as rated by engine manufacturer
†See Cub Cadet Yanmar Independent Dealer for warranty information



Sc2400 Specifications

POWERTRAIN

Gross HP	24 HP* diesel
PTO HP (Hyd)	16.5 at 3,200 RPM
Rated RPM	3,200 RPM
Number of cylinders	3
Bore and stroke	72 x 74 mm
Total displacement	55.1 cu. in.
Ignition type	Indirect injection
Lubrication	Full pressure
Oil filter	Spin-on/full flow
Cooling system	Liquid cooled
Air cleaner	4" single dry
Preheat system	Glow plug
Alternator	40 amp.
Exhaust	Right side pointing down

CAPACITIES

Fuel tank	5.8 gal.
Cooling system	3.4 qt.
Engine oil	2.5 qt.
Transmission case	2.0 gal.

DRIVETRAIN

Transmission type	Hydrostatic
Number of ranges	2 Shift-On-The-Go*
4WD operations	2WD & 4WD selectable
Cruise control	Selectable
Rear differential lock	Foot pedal operation
PTO type	Independent
Mid PTO/RPM (standard)	2,100/3,338
Rear PTO/RPM (standard)	540/3,111
Brake	Wet disc

MAXIMUM TRAVELING SPEED

Forward low	6.0 mph
Forward high	9.3 mph
Reverse low	3.6 mph
Reverse high	5.6 mph

HYDRAULICS

Type	Open center
Pump	Gear/Trochoid
Steering/SCV/3-pt hitch	3.5 GPM at 3,200 RPM
Transmission/hydraulic PTO	3.4 GPM at 3,200 RPM
Maximum pump capacity	6.9 GPM at 3,200 RPM
3-point hitch	Limited Category 1
3-point lift capacity at 24" behind	661 lbs.
Hydraulic control system	Position control

DIMENSIONS

Wheelbase	55.1"
Width	44.5" (w/R4)
Overall length w/3-pt hitch	95.5"
Ground clearance	7.5" (w/R4)
Weight w/ROPS & fluids	1,280 lbs.

TIRE SIZE

Front industrial/bar/turf	18" x 8.5" - 10"
Rear industrial/bar/turf	26" x 12.0" - 12"

RESIDENTIAL/COMMERCIAL WARRANTY†

Tractor	2-year or 2,000-hour limited warranty
Engine/drivetrain	5-year or 2,500-hour limited warranty

Sc2400 Attachment Specifications

CL100 CURVED BOOM LOADER

Maximum lift height at pivot point	71"
Dump clearance	54"
Reach at maximum height	27"
Maximum dump angle	45°
Reach w/bucket on ground	40"
Maximum rollback angle	25°
Digging depth	4"
Overall height in carry position	37"
Length of attachment (bucket bottom)	19.25"
Maximum lift height under bucket	66"
Bucket width/weight	48"/125 lbs.
Bucket capacity	5 cu. ft.
Lift capacity 500 mm forward of the pivot pins, maximum height	550 lbs.
Lift capacity at pivot pins, maximum height	700 lbs.
Breakout force at bucket pins	1,350 lbs.
Breakout force 500 mm forward of the pivot pins	1,050 lbs.
Raising time to full height w/o load	3.5 sec.
Lowering time w/o load (power down)	2.5 sec.
Attachment rollback time	2 sec.
Attachment dumping time	1.5 sec.
Rated flow	3.5 GPM
Relief valve	1,813 PSI

MM60RSe MID-MOUNT MOWER

Type	Side discharge
Mounting method	Suspended linkage
Lift linkage type	Parallel suspended
Transport height	6"
Number of blades	3
Cutting width	60"
Cutting height	1" - 4"
Height adjustment increment	Ground-contouring gauge wheels
Deck thickness	11-gauge reinforced edge

RESIDENTIAL/COMMERCIAL WARRANTY†

Attachments	1-year limited warranty
-------------	-------------------------

*as rated by engine manufacturer

†See your local Cub Cadet Yanmar Independent Dealer for warranty details.

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications. Please visit cubcadetyanmar.com for more information.