

## Z-FORCE®

HEAVY-DUTY  
ZERO-TURN RIDERS

Z-FORCE® 48

Z-FORCE® 54

### FEATURES

48" AND 54"  
TRIPLE-BLADE  
FABRICATED DECKS

WEIGHT 722 LBS. TO  
740 LBS.

DUAL HYDRO-GEAR™  
ZT-2800™ TRANSMISSION

4.25-GALLON FUEL TANK

ANTI-SCALPING WHEELS

ADJUSTABLE SEAT WITH  
GEL SUSPENSION

PIVOTING FRONT AXLE

FULLY WELDED STEEL  
FRAME

ARM RESTS ON  
ALL MODELS

PATENTED SMARTJET™  
DECK WASH SYSTEM

3-YEAR/180-HR LIMITED  
WARRANTY†

†See specifications for warranty information.



# WE PUT MORE IN IT. SO YOU'LL LOOK SMARTER FOR CHOOSING IT.

The Z-Force® zero-turn riders deliver more power and performance, so you can get the results you love — faster and easier. The zero turning radius means you'll work smarter. And with features like a pivoting front axle and high-back seat with gel suspension for comfort, you'll feel like you made the best decision.

INNOVATIVE FEATURES FOR AN INCREDIBLE EXPERIENCE. THAT'S THE CUB CADET ADVANTAGE.



### UNSURPASSED RESULTS OF THE CUB CADET SIGNATURE CUT™

A cutting system optimized by aerospace engineers, with a pivoting front axle that follows the contours of the ground for a smoother ride; and triple-blade, floating cutting deck for a flawless, professional-quality cut. Comes standard with heavy-duty fabricated decks.



### HEAVY-DUTY PERFORMANCE

The dedicated, dual hydrostatic rear-wheel transmission delivers effortless zero-turning control and minimized turfing.



### EASIER TO OPERATE

Foot-pedal deck height adjustment makes it easier to select and set preferred mowing height without stopping or leaving your seat.

LOCATE A DEALER AT  
**CUBCADET.COM**

INNOVATIONS NO ONE ELSE CAN DELIVER. AN EXPERIENCE NO ONE ELSE CAN MATCH. PROVE IT TO YOURSELF WITH A TEST DRIVE.

ENGINE	Z-FORCE® 48	Z-FORCE® 54
Engine Type	22 HP* Cub Cadet® professional-grade Kohler® Courage® PRO V-Twin* OHV	24 HP* Cub Cadet® professional-grade Kohler® Courage® PRO V-Twin* OHV
Engine Displacement/Orientation	725cc/vertical	725cc/vertical
Engine Fuel	Gas	
Lubrication/Filter	Full pressure w/spin-on oil filter	
Cooling System	Air	
Air Cleaner	Replaceable/dual element	
Alternator/Battery	12V – 15 amp. regulated/230 cca	
Wiring	Automotive-style	
Fuel capacity/Pod	Single 4.25-gallon tank/single storage pod	
<b>DRIVE SYSTEM</b>		
Transmission	Dual Hydro-Gear™ ZT-2800™ w/oil reservoir and filter	
Ground Speed	Fwd: 8 mph, rev: 3.5 mph	
Hydraulic Fluid	Rotella® Triple Plus 15W40	
Hydraulic Fluid Capacity	5.0 qt. (2.25 qt. per side including filter) including expansion tank	
Hydraulic Oil Filter	Standard	
Return to Neutral	Standard	
Braking/Parking Brake	Mechanical lever	
<b>STEERING</b>		
Controls	3-way adjustable lap bars	
Lap Bar Dampers	Standard	
Caster Wheel Pivot Bearings	Composite bushing	
Front Axle	Pivoting, steel	
<b>CHASSIS</b>		
Frame	Fully welded steel 1.5" x 2.0" tubular section	
<b>TIRES</b>		
Front Tire Size	13" x 5" – 6" (rib)	
Rear Tire Size	20" x 8" – 10" (turf)	20" x 10" – 10" (turf)
<b>DIMENSIONS</b>		
Length	70"	
Wheelbase	43"	
Weight (approx.)	722 lbs.	740 lbs.
<b>MOWER &amp; DECK DESIGN</b>		
Safety	Operator presence	
Deck Size	48"	54"
Deck Blades	Triple-blade/high lift blades standard	
Deck Construction	11-gauge fabricated deck, w/7-gauge reinforced top plate	
Deck Style/System	Floating	
Deck Drive	Belt driven, Kevlar®	
Deck Wash	Patented SmartJet™ high-pressure deck washing system	
Deck Lift	Foot-pedal, spring assisted	
Deck Height Adjustment	1.0" – 4.0" (in. 25" increments)	
Blade Spindle Construction	Cast aluminum with tapered roller bearings	
Greasable Spindle Bearings	Standard	
Blade Length	17"	19"
Blade Brake Clutch	Ogura GT-1	
Front Anti-Scalping Roller	Adjustable nose roller and 2 greasable anti-scalp wheels	
Rear Anti-Scalping Rollers/Striper	4 striping	
Deck PTO	Electronic fingertip engagement	
<b>ADDITIONAL SPECIFICATIONS</b>		
Monitor/Hour Meter	Standard	
Seat Type/Arm Rest	High-back w/arm rests and gel suspension	
Cup Holder	Standard—in storage pool	
Rear Hitch	Optional	
Foot Platform	Extruded steel	
<b>WARRANTY†</b>		
	3-year/180-hr limited warranty	

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.