

ENGINE	LGT 1054	LGTX 1050	LGTX 1054	GTX 1054
Engine Type	26 HP* Cub Cadet® professional-grade Kohler® V-Twin OHV	25 HP* Cub Cadet® professional-grade Kohler® V-Twin OHV	27 HP* Cub Cadet® professional grade Kohler® V-Twin OHV	27 HP* Cub Cadet® professional-grade Kohler® V-Twin OHV
Cylinders/Material	2/cast-iron sleeve			
Lubrication	Fully pressurized automotive-style oil pump w/spin-on oil filter			
DRIVE SYSTEM				
Drive System	Automatic w/heavy-duty hydrostatic pump			
Engine to Transmission	Heavy-duty belt			
Cruise Control	Standard			
Transmission Housing	Die-cast aluminum			
STEERING				
Steering Assist	Manual sector and pinion	Electronic Power Steering (EPS)	Electronic Power Steering (EPS)	Electronic Power Steering (EPS)
Front Axle	Heavy-duty cast-iron — 5-year limited warranty			
Spindles	3/4" w/grease fittings			
Ball Joints	2 automotive-style			
Rear Axle Diameter	3/4" diameter with dual steel wheel drive hubs	3/4" diameter with dual steel wheel drive hubs	3/4" diameter with dual steel wheel drive hubs	1" diameter with dual steel wheel drive hubs
Turning Radius	12"	12"	12"	18"
CHASSIS				
Chassis Type	Robotically welded frame assembly			
Frame	Heavy-duty 9-gauge steel frame rails — 5-year limited warranty			
Hood & Grill	Corrosion- and dent-resistant high-impact ABS			
Fender & Bumper	Steel fender w/twin rear fender flares w/grab handles and GT-style twin-tube steel bumper			
ELECTRICAL SYSTEM				
Alternator	15 amp. regulated	25 amp. regulated	25 amp. regulated	25 amp. regulated
Battery	12V/heavy-duty 230 cold crank amp.	12V/heavy-duty 260 cold crank amp.	12V/heavy-duty 260 cold crank amp.	12V/heavy-duty 260 cold crank amp.
Charging System	Flywheel alternator			
Headlights	Standard			
System Monitor Package	Digital hour meter, change oil service minder, battery voltage monitor, park brake and PTO start sequence LEDs			
Safety Systems	Neutral start, operator presence, reverse safety switch, brake pedal lock, RevTEK™ reverse mowing technology			
OPERATION				
PTO Clutch	Electronic fingertip engagement for smooth operation of deck or attachments			
Deck Lift	Manual/12-position/spring-assisted			
Brakes	Automotive-style disc			
Seat	Cub Comfort™ high-back seat, 12-position fingertip adjustment mechanism with 6" seat travel			
ADDITIONAL SPECIFICATIONS				
Front Tires	16" x 6.5"	16" x 6.5"	16" x 6.5"	16" x 7.5"
Rear Tires	22" x 9.5"	22" x 9.5"	22" x 9.5"	23" x 10.5"
Forward Speed	0 – 5.2 mph			
Reverse Speed	0 – 2.3 mph			
Fuel Tank Capacity	3.3 gal. easy fill, rustproof			
Engine Oil Capacity	1.9 qt.			
Transmission Oil Capacity	2.0 qt.	2.0 qt.	2.0 qt.	2.1 qt.
Wheelbase	47.5"	47.5"	47.5"	49"
Overall Length	69"	69"	69"	68"
Estimated Weight w/Deck	567 lbs.	548 lbs.	567 lbs.	587 lbs.
MOWER DECK				
Cutting Width/Blades	54" heavy-duty triple blades	50" heavy-duty triple blades	54" heavy-duty triple blades	54" heavy-duty triple blades
Deck Cutting Height	1.5" – 4"			
Deck Construction	12-gauge steel	12-gauge steel	11-gauge steel	11-gauge steel
Deck Drive System	Heavy-duty Kevlar® belt			
Anti-scalping	4 wheels	4 wheels	4 wheels	4 wheels, 1 rear striping roller
Mulch Kit	Optional			
Deck Spindles	Die-cast aluminum spindle housings w/ball bearings for long life			
Deck Pulleys	All steel w/heavy-duty bearings			
Deck Attach/Removal	QuickAttach™ in seconds, no tools required			
Deck Wash	Patented SmartJet™ high-pressure deck washing system			
WARRANTY*				
	3-year/120-hr and 5-year/500-hr limited warranty			



*Cub Cadet will provide a limited warranty for a period of 5 years or 500 hours, whichever occurs first, for the frame and pivoting cast-iron front axle on all new Cub Cadet Series 1000 Tractors. For complete details on 3-year and 5-year limited warranties, see your Cub Cadet Independent Dealer or operator's manual. 3 years or 120 hours, whichever comes first. Warranty does not cover normal wear on parts, batteries, and frame and front axle. Frame and front axle are covered for 5 years or 500 hours, whichever comes first. See operator's manual for details on Cub Cadet's Manufacturer's Limited Warranty for Series 1000 Lawn Tractors.

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine. Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications. *as rated by engine manufacturer †See your local Cub Cadet Independent Dealer for warranty details.

773-05145 Printed in U.S.A. 12/12 © 2013 Cub Cadet



SERIES 1000

- LTX 1040
- LTX 1042 KW
- LTX 1045
- LTX 1046
- LTX 1046 KW
- LTX 1050
- LTX 1050 KW
- LGT 1050
- LGT 1054
- LGTX 1050
- LGTX 1054
- GTX 1054

DESIGNED FOR LAWN AND YARD CARE UP TO 3 ACRES.

FEATURES

ELECTRONIC POWER STEERING (EPS)
(on select Series 1000 models)

42", 46" TWIN-BLADE DECKS AND 50", 54" TRIPLE-BLADE DECKS

CRUISE CONTROL

HEAVY-DUTY 9-GAUGE STEEL FRAME RAILS

PADDED FOOT RESTS

FENDER FLARES WITH GLOVE BOX

PATENTED SMARTJET™ DECK WASH SYSTEM

OPTIONAL ATTACHMENTS AND ACCESSORIES AVAILABLE

ACCURATE EASY-TO-READ FUEL GAUGE

3- AND 5-YEAR LIMITED WARRANTY†

†See specifications for warranty information.

cubcadet.com



URNS BETTER. CUTS BETTER. FLAT OUT BETTER.

The Series 1000 is the most advanced lawn tractor in its class. Starting with the Cub Cadet Signature Cut™ for a flawless, professional-quality cut every time. With an ultra-tight turning radius and available Electronic Power Steering, you'll have more precision control than ever. Only Cub Cadet could make it so easy to maneuver around landscaping and enjoy all-day comfort.

SMARTER FEATURES FOR A BETTER EXPERIENCE. THAT'S THE **CUB CADET ADVANTAGE.**



UNSURPASSED RESULTS OF THE CUB CADET SIGNATURE CUT™

Aerospace engineers developed an advanced cutting system with optimal airflow, blade overlap and floating deck for a perfect cut. The addition of anti-scalping wheels and rear striping rollers (on select models) will deliver a professional-quality finish that will make you the envy of the neighborhood.



REMARKABLE MANEUVERABILITY AND COMFORT

Feel the difference at your fingertips from the only tractor in its class to feature an ultra-tight turning radius, power steering (on select models), and rider-control comfort for all-day ease of use.



LEGENDARY CUB CADET PERFORMANCE AND DURABILITY

Enjoy caring for your lawn with confidence. Only Cub Cadet combines features like a fully welded steel frame with the thickest gauge steel in its class, high-performance professional grade engines and an unbeatable 5-year factory warranty.

LOCATE A DEALER AT **CUBCADET.COM**

INNOVATIONS NO ONE ELSE CAN DELIVER. AN EXPERIENCE NO ONE ELSE CAN MATCH. PROVE IT TO YOURSELF WITH A TEST DRIVE.

ENGINE	LTX 1040	LTX 1042 KW	LTX 1045
Engine Type	19 HP* Cub Cadet® professional-grade Kohler® single-cylinder OHV	18 HP* Cub Cadet® professional-grade Kawasaki® V-Twin OHV	20 HP* Cub Cadet® professional-grade Kohler® single-cylinder OHV
Cylinders/Material	1/cast-iron sleeve	2/cast-iron sleeve	1/cast-iron sleeve
Lubrication	Fully pressurized automotive-style oil pump w/spin-on oil filter		

DRIVE SYSTEM			
Drive System	Automatic CVT w/cruise control	Automatic Tuff Torq™ transmission w/heavy-duty hydrostatic pump	Automatic w/heavy-duty hydrostatic pump
Engine to Transmission	Twin CVT drive belt	Heavy-duty belt	Heavy-duty belt
Cruise Control	Standard		
Transmission Housing	Die-cast aluminum		

STEERING			
Steering	Manual sector & pinion		
Front Axle	Heavy-duty cast-iron w/dual grease fittings – 5-year limited warranty		
Spindles	3/4"		
Ball Joints	2 automotive-style		
Rear Axle Diameter	3/4" diameter with dual steel drive hubs		
Turning Radius	12"		

CHASSIS			
Chassis Type	Robotically welded frame assembly		
Frame	Heavy-duty 9-gauge steel frame rails – 5-year limited warranty		
Hood & Grill	Corrosion- and dent-resistant high-impact ABS		
Fender & Bumper**	Steel fender w/grab handles	Steel fender w/grab handles and glove box + bumper	Steel fender w/grab handles and glove box

ELECTRICAL SYSTEM			
Alternator	15 amp. regulated		
Battery	12V/H.D. 190 cold crank amp	12V/H.D. 230 cold crank amp	12V/H.D. 190 cold crank amp
Charging System	Flywheel alternator		
Headlights	Standard		
System Monitor Package	Digital hour meter, change oil service minder, battery voltage monitor, park brake and PTO start sequence LEDs		
Safety Systems	Neutral start, operator presence, reverse safety switch, brake pedal lock, RevTEK™ reverse mowing technology		

OPERATION			
PTO Clutch	Manual lever control		
Deck Lift	Manual/12-position		
Brakes	Automotive-style disc		
Seat	Cub Comfort™ mid-back seat, 12 positions with 6" seat travel	Cub Comfort™ high-back seat, 12 positions with 6" seat travel	Cub Comfort™ high-back seat, 12 positions with 6" seat travel

ADDITIONAL SPECIFICATIONS			
Front Tires	15" x 6"		
Rear Tires	20" x 8"		
Forward Speed	0 – 5.2 mph		
Reverse Speed	0 – 5.2 mph	0 – 2.3 mph	0 – 2.3 mph
Fuel Tank Capacity	3.3 gal. easy fill, rustproof		
Engine Oil Capacity	1.6 qt.		
Transmission Oil Capacity	19 oz.	1.9 qt.	1.9 qt.
Wheelbase	47.5"		
Overall Length	69"		
Estimated Weight w/Deck	468 lbs.	498 lbs.	510 lbs.

MOWER DECK			
Cutting Width/Blades	42" heavy-duty twin blades	42" heavy-duty twin blades	46" heavy-duty twin blades
Deck Cutting Height	1.5" – 4"		
Deck Construction	12-gauge steel		
Deck Drive System	Heavy-duty Kevlar® belt		
Anti-scalping	4 wheels		
Mulch Kit	Optional		
Deck Spindles	Die-cast aluminum spindle housings w/ball bearings for long life		
Deck Pulleys	All steel w/heavy-duty bearings		
Deck Attach/Removal	QuickAttach™ in seconds, no tools required		
Deck Wash	Patented SmartJet™ high-pressure deck washing system		

WARRANTY†			
3-year/120-hr and 5-year/500-hr limited warranty			

ATTACHMENTS MAKE A SMART CHOICE EVEN SMARTER.

Twin and triple bagger, mulch kit, rear spreader, lawn sweeper, steel cart, poly cart, lawn dethatcher, lawn spike and plug aerator, lawn roller, electric sleeve hitch (Series 1000 GT only), hydraulic tiller (Series 1000 GT only), rear bracket & weight kit, wheel weights, suitcase weights, tire chains, snow thrower and snow blade.

* as rated by engine manufacturer

** Front bumper standard on LTX 1042 KW, LTX 1046 KW & LTX 1050 KW.

† See your local Cub Cadet Independent Dealer for warranty details.

ENGINE	LTX 1046	LTX 1046 KW	LTX 1050 KW	LTX 1050	LGT 1050
Engine Type	22 HP* Cub Cadet® professional-grade Kohler® V-Twin OHV	21.5 HP* Cub Cadet® professional-grade Kawasaki® V-Twin OHV	23 HP* Cub Cadet® professional-grade Kawasaki® V-Twin OHV	24 HP* Cub Cadet® professional-grade Kohler® V-Twin OHV	25 HP* Cub Cadet® professional-grade Kohler® V-Twin OHV
Cylinders/Material	2/cast-iron sleeve				
Lubrication	Fully pressurized automotive-style oil pump w/spin-on oil filter				

DRIVE SYSTEM					
Drive System	Automatic w/heavy-duty hydrostatic pump	Automatic Tuff Torq™ transmission w/heavy-duty hydrostatic pump	Automatic Tuff Torq™ transmission w/heavy-duty hydrostatic pump	Automatic w/heavy-duty hydrostatic pump	Automatic w/heavy-duty hydrostatic pump
Engine to Transmission	Heavy-duty belt				
Cruise Control	Standard				
Transmission Housing	Die-cast aluminum				

STEERING					
Steering	Manual sector & pinion				
Front Axle	Heavy-duty cast-iron w/dual grease fittings – 5-year limited warranty				
Spindles	3/4"				
Ball Joints	2 automotive-style				
Rear Axle Diameter	3/4" diameter with dual steel drive hubs				
Turning Radius	12"				

CHASSIS					
Chassis Type	Robotically welded frame assembly				
Frame	Heavy-duty 9-gauge steel frame rails – 5-year limited warranty				
Hood & Grill	Corrosion- and dent-resistant high-impact ABS				
Fender & Bumper**	Steel fender w/grab handles and glove box	Steel fender w/grab handles and glove box + bumper	Steel fender w/grab handles and glove box + bumper	Steel fender w/grab handles and glove box	Steel fender w/grab handles and glove box

ELECTRICAL SYSTEM					
Alternator	15 amp. regulated				
Battery	12V/H.D. 230 cold crank amp.	12V/H.D. 230 cold crank amp.	12V/H.D. 230 cold crank amp.	12V/H.D. 230 cold crank amp.	12V/H.D. 235 cold crank amp.
Charging System	Flywheel alternator				
Headlights	Standard				
System Monitor Package	Digital hour meter, change oil service minder, battery voltage monitor, park brake and PTO start sequence LEDs				
Safety Systems	Neutral start, operator presence, reverse safety switch, brake pedal lock, RevTEK™ reverse mowing technology				

OPERATION					
PTO Clutch	Manual lever control	Electronic fingertip engagement for smooth operation of deck or attachments	Electronic fingertip engagement for smooth operation of deck or attachments	Electronic fingertip engagement for smooth operation of deck or attachments	Electronic fingertip engagement for smooth operation of deck or attachments
Deck Lift	Manual/12-position	Manual/12-position	Manual/12-position	Manual/12-position	Manual/12-position/spring-assisted
Brakes	Automotive-style disc				
Seat	Cub Comfort™ high-back seat, 12 positions with 6" seat travel				

ADDITIONAL SPECIFICATIONS					
Front Tires	15" x 6"	15" x 6"	15" x 6"	15" x 6"	16" x 6.5"
Rear Tires	20" x 8"	20" x 8"	20" x 10"	20" x 8	22" x 9.5"
Forward Speed	0 – 5.2 mph				
Reverse Speed	0 – 2.3 mph				
Fuel Tank Capacity	3.3 gal. easy fill, rustproof				
Engine Oil Capacity	1.9 qt.				
Transmission Oil Capacity	2.0 qt.				
Wheelbase	47.5"				
Overall Length	69"				
Estimated Weight w/Deck	513 lbs.	513 lbs.	548 lbs.	548 lbs.	

MOWER DECK					
Cutting Width/Blades	46" heavy-duty twin blades	46" heavy-duty twin blades	50" heavy-duty triple blades	50" heavy-duty triple blades	50" heavy-duty triple blades
Deck Cutting Height	1.5" – 4"				
Deck Construction	12-gauge steel				
Deck Drive System	Heavy-duty Kevlar® belt				
Anti-scalping	4 wheels				
Mulch Kit	Optional				
Deck Spindles	Die-cast aluminum spindle housings w/ball bearings for long life				
Deck Pulleys	All steel w/heavy-duty bearings				
Deck Attach/Removal	QuickAttach™ in seconds, no tools required				
Deck Wash	Patented SmartJet™ high-pressure deck washing system				

WARRANTY†					
3-year/120-hr and 5-year/500-hr limited warranty					